

Product Information Bulletin

PENTRON PREMIER™ XP ECOLOGIC® LAMPS

T5 Linear Fluorescent Lamps



A dramatic improvement in the developing line of slender, 5/8" diameter, T5 linear fluorescent sources, the PENTRON PREMIER XP ECO® lamps provide increased lumen output, the highest in the industry, with an astonishing 111 lamp lumens per watt

Greater system flexibility is achieved when PENTRON PREMIER XP lamps are combined with the new series of OSRAM SYLVANIA QUICKTRONIC PENTRON ballasts achieving a varied lumen package depending upon the application.

PENTRON PREMIER XP lamps also present the greatest opportunity for luminaire efficiency. The 5/8" diameter affords superior optical control achieving precision distribution in a well designed luminaire.

Application Information

Applications

Office
Schools
Commercial
Retail
Hospitality
Institutional
New Construction
Renovation

- Improved phosphor blend yields brighter PENTRON PREMIER XP lamps
 - 3125 lumens at 35°C for FP28/PM/XP lamps
- QUICK 60+® system warranty when operated on OSRAM SYLVANIA QUICKTRONIC® ballasts including the .90BF, .95BF, 1.15BF and QUICKSTEP® T5 ballasts
 - Multiple ballast factor choices, including a stepped switching ballast provide design flexibility as well as extreme system efficiency (as high as 104 LPW)
- Passes the Federal TCLP test
- 3000K, 3500K, 4100K and 85 CRI
- 95% lumen maintenance
- 20,000 hours average rated life

SYLVANIA PENTRON PREMIER XP ECOLOGIC fluorescent lamps pass the Federal Toxicity Characteristic Leaching Procedure (TCLP) criteria¹ for classification as non-hazardous waste in most states².



1. TCLP test results are based on NEMA LL Series standards and are available on request.
2. Lamp disposal regulations may vary; check your local & state regulations.

Product Availability

NAED Code	Ordering Description
21060	FP28/830/PM/XP/ECO
21057	FP28/835/PM//XP/ECO
21058	FP28/841/PM/XP/ECO

Application Notes

1. PENTRON PREMIER XP lamps are about 2" shorter than T8 and T12 bi-pin lamps.
2. Miniature bi-pin (T-5) base will not install into T8 and T12 sockets.
3. Miniature bi-pin (T-5) base requires UL listed 600 Volt rated sockets.
4. Requires high-frequency programmed rapid start electronic ballasts equipped with end-of-life sensing circuit
5. Apply thermal factor in calculations for exterior or unheated applications.

Sample Specification

Lamp(s) shall be PENTRON PREMIER™ XP ECO® T5 lamps having 2730 rated lumens at 25°C, 3050 lumens at 35°C and 95% lumen maintenance. Lamps shall have a correlated color temperature of (3000K, 3500K, 4100K) and a color rendering index of 85. Lamps shall be operated on OSRAM SYLVANIA QUICKTRONIC® ballast and a complete system warranty from a single manufacturer shall cover both lamps and ballasts.

Lamp System Comparison

Lamp	Ballast	Input Watts	Initial System Lumens	Initial System LPW	Avg. Rated Life
F34T12	ES Magnetic	72	4660	65	20,000
F32T8/700 - 3 lamps	3 Lamp IS	88	7525	86	15,000
FP28PM/XP/ECO	QHES2X28/UNV PS90SC	55/54	5625	102/104	20,000
FP28PM/XP/ECO	QHES2X28/UNV PS90SC	27*	2185	80	

*operated at 50% Power

Ordering and Specification Information

NAED Number	Ordering Abbreviation	Base	Watts	Initial Lumens @25°C	Initial Lumens @35°C	Bulb	Nominal Length (mm)	Avg. Rated Life	Color Temp	CRI
21060	FP28/830/PM/XP	Min Bi-pin	28	2800	3125	T5	1149	20,000	3000	85
21057	FP28/835/PM/XP	Min Bi-pin	28	2800	3125	T5		20,000	3500	85
21058	FP28/841/PM/XP	Min Bi-pin	28	2800	3125	T5		20,000	4100	85

OSRAM SYLVANIA National Customer Support Center 18725 N. Union Street Westfield, IN 46074


1-800-LIGHTBULB (1-800-544-4828)

Visit our website: www.sylvania.com

Ordering Guide

FP	28	/	8	/	35	/	PM XP	/	ECO®
Fluorescent	Wattage:		CRI		30=3000K		PENTRON		ECOLOGIC®
PENTRON®	28 watts		8 = 85		35=3500K		PREMIER™ XP		
T5					41=4100K				

Dimensions



Lamp	(A) Max Overall Length in (mm)	(B) (C) Max Base Face To Opposite Pin in (mm)	Max Base Face To Base Face in (mm)	(D) Max Outside Diameter in (mm)
FP28	45.80 (1163.2)	45.52 (1156.1)	45.24 (1149.0)	0.67 (17.0)

Technical Information

